


Countersinks for 2 flutes dowel drills


315


D ₂ mm	D mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
From 5 to 10	20		315.200.11	315.200.12
From 11 to 12	22		315.220.11	315.220.12

Spare parts

M5x5mm screw	990.006.00
2,5mm allen key	991.062.00

For assembly on the shank of the drill.


For use with the following parts: 310-311-362-313-314-366 HW

TECHNICAL DETAILS:

- Super-strength steel
- 2 precision ground carbide tipped cutting edges [Z2]
- Direct clamp on the shank of the drills.

APPLICATION: used for chamfering and drilling in solid wood, wood composites, plastic and laminated materials.

Countersinks for 4 flutes dowel drills


316


D ₂ mm	D mm		ORDER NO. Right-hand rotation	ORDER NO. Left-hand rotation
4	16		316.040.11	316.040.12
5	16		316.050.11	316.050.12
6	16		316.060.11	316.060.12
7	16		316.070.11	316.070.12
8	18		316.080.11	316.080.12
9	18		316.090.11	316.090.12
10	20		316.100.11	316.100.12
12	20		316.120.11	316.120.12

TECHNICAL DETAILS:

- Super-strength steel
- 2 HW precision ground cutting edges [Z2]

APPLICATION: used for drilling and chamfering in solid wood, wood composites, plastic and laminated materials.

Spare parts

M5x5mm screw	990.002.00
2,5mm allen key	991.062.00

For assembly on the spiral head of the bit. Adjustable depth.

For use with the following parts:

306-307-308-309-373-374-375-338-339-340-341-342-343-344-346-352-353 HW

315 assembly Illustration



316 assembly Illustration

